

TempTec 332

DESCRIPTION AND GENERAL PROPERTIES

- Material Neoprene
- Length (cm) 35.5
- Thickness (mm)
- Colour/Color Black / Blue
- Interior finish Knitted thermal protection
- Exterior finish Pebbled
- Size / EAN 8 9 10
- Packaging 1 pair/bag - 6 pairs/carton
- Complementary information Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 3

CE 0334



Dexterity EN 420 : 5/5

111



X2XXXX



ACLMNS



2212X

Type A

Legends



MECHANICAL HAZARDS EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
 Abrasion resistance
 Blade cut resistance
 Tear resistance
 Puncture resistance



LOW CHEMICAL PROTECTION EN 374



MICRO-ORGANISMS EN 374



RADIOACTIVE CONTAMINATION EN 421



HEAT AND FIRE EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 Burning behaviour
 Contact heat resistance
 Convective heat resistance
 Radiant heat resistant
 Resistance to small drops of molten metal
 Resistance to large quantities of molten metal



SPECIFIC CHEMICAL PROTECTION EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofuran
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



COLD HAZARDS EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 Convective cold resistance
 Contact cold resistance
 Water permeability

For more details: www.mapa-pro.com

MAPA[®]
PROFESSIONAL

www.mapa-pro.com

SPECIFIC ADVANTAGES

- Multi-purpose chemical resistance (acids, aliphatic solvents) increased by the thickness of the material
- Excellent thermal insulation, due to double-knit cotton
- Good grip of wet or slippery objects, due to embossed texture
- Previous name: Temp-Tec 332 (NL-56)

MAIN FIELDS OF USE

Petrochemical industry

- Sampling of hot petrochemical products

Rubber industry

- Polymer extrusion

Other industries

- Steam cleaning
- Road works in cold conditions
- Manufacture of insulating electric wires
- Boiler room work
- Manufacture of adhesives
- Handling of moulds in the ceramic industry
- Handling of hot piping

Mechanical industry

- Chemical treatment of metals
- Oil quenching of steel

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests. For very high or low temperatures, be careful that a sustained contact does not cause burns.
- It is not recommended to use this glove next to moving machinery
- It is not recommended for persons sensitized to dithiocarbamates to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONAL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Ensure the inside of the gloves is dry before putting them on again.

Storage conditions

- Store the gloves in their original packaging at a temperature not below 5°C.

Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
- in use with a solvent (diluent, etc...) : rub over with a dry cloth
- in use with acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth
- Caution : improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

Food contact US

- FDA 21CFR 177.2600

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0075/014/162/05/19/1646
- **Issued by the notified body nr** : 0075 - CTC – 4, rue . Hermann Frenkel -69367 LYON cedex 07- France
- **Quality assurance certificat** : 0334 Asqual 14 rue des Reculettes -F-75013 PARIS