



# SAFETY JOGGER

## PROFESSIONAL



Medium

## ELA 01

Sporty and trendy sneaker for her

Upper	Synthetic Leather
Lining	Mesh
Footbed	SJ foam footbed
Outsole	PU/Rubber
Safety standard	O1 / ESD, SRC
Size range	EU 35-42 / UK 3.0-8.0 US 5.5-10.5 / CM 23.0-27.0
Sample weight	0.336 kg
Norms	EN ISO 20347:2012 ASTM F2892:2018



LIC



FUX

LBL

LGN

LGR




### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



### Memory foam

The removable memory foam insole provides extra comfort during stepping and can be exchanged with your own orthopedic sole.



### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



## Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED IN EUROPE

www.safetyjogger.com

**Industries:**

Catering, Cleaning, Food &amp; beverages, Medical

**Environments:**

Dry environment, Extreme slippery surfaces

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Synthetic Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	1.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	17.0	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	33.3	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	266.5	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
<b>Outsole</b>	<b>PU/Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	124	≤ 150
	Outsole slip resistance SRA: heel	friction	0.48	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.57	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.15	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	0.32	0.1 - 1000
	ESD value	MegaOhm	74	0.1 - 100
	Heel energy absorption	J	38	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.