



by Honeywell

Technical Specifications

PSS RESTRAINT ROPE LANYARD 1M MOB.PLATF

Description :

PA 3 strand TITAN lanyard Ø12mm, length 1m equipped with 1 screwgate karabiner CS20 & 1 steel scaffold hook, opening 50mm

Reference : 1031453

Features :

Rope :

Raw Material : 3 strand polyamide rope
Breaking strength: > 2200 daN

CS20 connector:

Raw Material: steel
Opening: 17mm
Weight: 0.165 kg
Dimensions : 104 x 58 mm

Scaff Hook connector :

Raw Material: steel
Opening : 50 mm
Weight : 0.165 kg
Dimensions : 218 x 115 mm

Weight : 0.900 kg

Temperature: -30°C to +50°C

EN 354



LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com