

Battery Charger XGT®

191E08-6

Li-ion • 40Vmax • DC40RA

Charger for XGT® 40Vmax batteries.

Rapid charger for XGT® 40Vmax slide-style batteries. Cooling fans cool the battery and charger circuit board during charging, allowing faster charging. Charging optimised in terms of voltage, current and temperature. Charges a battery in 28-45 minutes, depending on the battery's capacity.



Technical specifications

| | |
|---------------------------------|-------------------|
| Voltage XGT | ✓ |
| Nominal Battery Voltage | 40 V |
| Average Charging Time | 22 - 50 min |
| Charging Time 2.0 Ah | 22 min |
| Charging Time 2.5 Ah | 28 min |
| Charging Time 4.0 Ah | 45 min |
| Charging Time 5.0 Ah | 50 min |
| Charging Time 8.0 Ah | 76 min |
| Continuous Input Power | 310 W |
| Product net weight | 1,0 kg |
| Product Dimensions (L x W x H): | 156 x 210 x 84 mm |
| Power Supply Cord | 2,0 m |

User benefits

- Developed for charging XGT Li-Ion batteries
- Equipped with two cooling fans, one for battery and the other for charging circuit
- Compatible with Interchangeable adapter ADP10 for charging LXT Li-Ion batteries
- New charging status indicator light, enlarged and raised for clearer indication
- Selectable melody sound for full charge notification
- Also works as a wall-mounted charger
- Able to perform consecutive fast charging of batteries

Link to product - www.makita.com



Related products

■ Other

User manual

Parts drawing