

2977Q



Telescopic handle only for  
condensation squeegee  
7716x(Q), 74.02 - 236.22",  
Ø1.34, Grey



Ideal for removing condensation from ceilings and pipes, this telescopic fibreglass handle is used with the condensation squeegee (7716). Cannot be used as a waterfed handle.

# Technical Data

<b>Item Number</b>	2977Q
<b>Material</b>	Fibreglass Polypropylene Chromium-plated brass
<b>Meets the REACH Regulation (EC) No. 1907/2006</b>	Yes **
<b>SCIP number</b>	e49c50b5-7653-429c- b8f3-803d37b5fefc
<b>Use of phthalates and bisphenol A</b>	No
<b>Is Halal and Kosher compliant</b>	Yes
<b>Box Quantity</b>	1 Pcs.
<b>Quantity per Pallet (80 x 120 x 200 cm)</b>	99 Pcs.
<b>Quantity Per Layer (Pallet)</b>	11 Pcs.
<b>Product diameter</b>	1,34 "
<b>Length</b>	74,02 "
<b>Width</b>	1,34 "
<b>Height</b>	1,34 "
<b>Max. Length</b>	236,22 "
<b>Net Weight</b>	4,0564 lbs
<b>Tare Cardboard</b>	0,56 lbs
<b>Tare Total</b>	0,56 lbs
<b>Gross Weight</b>	4,6186 lbs
<b>Cubic Feet</b>	0,0768 ft3
<b>Recommended sterilisation temperature (Autoclave)</b>	212 °F
<b>Max usage temperature (non food contact)</b>	176 °F
<b>Min. pH-value in usage concentration</b>	2 pH
<b>Max. pH-value in Usage Concentration</b>	10,5 pH
<b>GTIN-13 Number</b>	5705020297748
<b>GTIN-14 Number (Box quantity)</b>	15705020297745
<b>Customs Tariff No.</b>	96039010
<b>Country of Origin</b>	Finland
<b>Box length</b>	77,95 "
<b>Box Width</b>	2,36 "
<b>Box Height</b>	2,36 "

New equipment should be cleaned, disinfected, sterilised and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

\*\* Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead. This product is

registered in the EU SCIP database. Please find SCIP number above.

3. Do not store the product below 32 °Fahrenheit.