Telephone: 0044 (0)28 8772 2940

Clear Latex Powder Free Examination Glove

DC31 Clear (Textured)

- 1.1 **TYPE** Latex Examination Glove, Powderfree, On-Line Chlorination, Non-sterile
- 1.2 **MATERIAL** Natural High Grade Rubber Latex.
- 1.3 **COLOUR** Off white to yellow.

BODYTECH

- 1.4 DESIGN AND FEATURE Ambidextrous, textured, beaded cuff
- 1.5 **POWDER** No powder lubricant added.
- 1.6 **STORAGE CONDITION** The gloves shall maintain their properties. when stored in a dry condition. Avoid direct sunlight.
- 1.7 **SHELF-LIFE** The gloves shall have shelf life of 5 years from the date of manufacture with the above storage condition.
- 1.8 **PACKING STYLE** 100 pcs gloves x 10 dispensers x 1 carton.
- 1.9 **SIZE MARKING** The size of gloves shall be marked in the check box on every carton with black ink.

PERFORMANCE REQUIREMENTS

(Sampling Plan - ISO 2859 Single Normal)

(Sam	ipling Plan – ISO 2859 Single No			
	Characteristics	Inspection Level	Acceptable Quality Level	Reference Standard
2. 1	Dimensions	S2	4.0	ASTM D3578-05
2. 2	Physical Properties	S2	4.0	In-house practice
2. 3	Freedom from Holes (Water Tight Test)	GI	1.5	In-house practice
2. 4	Visual Defects:			
(i)	Major Visual	GI	2.5	In-house practice
(ii)	Minor Visual		4.0	
2.5 P	ackaging Defects:			
(i)	Regulatory	GI	**	
(ii)	Visual	GI	4.0	In-house Inspection
(iii)	Critical (incl. Gloves counting)	S2	4.0	
2.6	Powderfree Residue	N=5	-	ASTM D3578-05
				ASTM D6124-06
0.7		Nist slisses d		





Dimensions

Description	Size	Standard
Length (mm)	All Sizes	Min 240
Palm Width (mm)	S M L XL	84 +/- 3 94 +/- 3 105 +/- 3 113 +/- 3
Thickness * single wall	All Sizes	Finger 0.12 +/- 0.02 (Typical value: 0.11 - 0.14) Palm 0.11 +/- 0.02 (Typical value: 0.10 - 0.12)

Physical Properties

Description	Standard		
	Before Aging	After Aging	
Median Force at Break (%)	Min 550 (Typical value: 550 - 800)	Min 450 (Typical value: 450 - 600)	
Tensile Strength (MPa)	Min 16 (Typical value: 16-22)	Min 12 (Typical value: 12-18)	



Freedom from holes

The sample size and allowable number of non-conforming gloves in the samples shall be determined in accordance to Sampling Plan ISO 2859-1 Single Normal using inspection and acceptable quality level as stated in Section II: Performance Requirements.

Visual Defects

The sample size and allowable number of non-conforming gloves in the samples for both major and minor defects shall be determined in accordance to Sampling Plan ISO 2859-1 Single Normal using inspection and acceptable quality level as stated in Section II: Performance Requirements.

Packaging Defects

The Sample size and allowable number of non-conforming in the samples for regulatory, visual and critical packaging defects shall be determined in accordance to Sampling Plan ISO 2859-1 Single Normal using inspection and acceptable quality level as stated in Section II: Performance Requirements (Gloves Counting=100 pcs by weight per Dispenser).

Powderfree Residue

Maximum 2 mg per glove



