






## Orthomat® Premium

Reduces standing fatigue for those that move at work



- Exceptional fatigue-relief properties – a real investment for the workplace.
- Dual layer construction for superior comfort and durability.
- Tough textured top surface for excellent resilience against wear and tear.
- Insulates against the effects of cold concrete floors.
- Low density underlayer provides extremely effective underfoot cushioning.
- Tapered edges to reduce trip hazards.
- Range of colours available.
- Ideal for demanding environments where regular turning is involved.
- Fire tested to BS EN 13501-1.



Styles Available



Green



Blue



Black



Black / Yellow - NEW!

## Parts

| Part Number | Size                     | Colour       | Weight (kg) |
|-------------|--------------------------|--------------|-------------|
| FF010703C   | 0.9 m x per linear metre | Black/Yellow | 1.35        |
| FF010703    | 0.9 m x 18.3 m           | Black/Yellow | 24.71       |
| FF010702    | 0.9 m x 1.5 m            | Black/Yellow | 2.03        |
| FF010701    | 0.6 m x 0.9 m            | Black/Yellow | 0.81        |
| FF040005    | 1.2 m x 18.3 m           | Green        | 88          |
| FF040003C   | 0.9 m x per linear metre | Green        | 3.8         |
| FF040003    | 0.9 m x 18.3 m           | Green        | 61          |
| FF020003C   | 0.9 m x per linear metre | Blue         | 3.8         |
| FF020003    | 0.9 m x 18.3 m           | Blue         | 61          |
| FF010006C   | 1.2 m x per linear metre | Black        | 5.1         |
| FF010006    | 1.2 m x 18.3 m           | Black        | 93.5        |
| FF010005C   | 0.6 m x per linear metre | Black        | 2.49        |
| FF010005    | 0.6 m x 18.3 m           | Black        | 45.6        |
| FF010004    | 0.9 m x 3.65 m           | Black        | 12.15       |
| FF010003C   | 0.9 m x per linear metre | Black        | 3.8         |
| FF010003    | 0.9 m x 18.3 m           | Black        | 61          |
| FF010002    | 0.9 m x 1.5 m            | Black        | 4.99        |
| FF010001    | 0.6 m x 0.9 m            | Black        | 2           |

## Technical Specifications

|                            |                                                                                  |
|----------------------------|----------------------------------------------------------------------------------|
| Material                   | Open Cell PVC (Foam)                                                             |
| Surface Finish             | Tough Textured top surface                                                       |
| Product Height             | 12.5 mm                                                                          |
| Roll Length                | 18.3 m                                                                           |
| Min. Operating Temperature | 0°C                                                                              |
| Max. Operating Temperature | +60°C                                                                            |
| Resistance to Chemicals    | Resistant to most chemicals                                                      |
| Environmental Resistance   | Suitable for dry indoor environments                                             |
| Typical Applications       | Production lines, Assembly areas, Packing stations, Workbenches, Retail counters |
| Installation Method        | Loose lay                                                                        |
| Accessories                | Bevelled edging                                                                  |
| Cleaning Method            | Brush/mop the top surface                                                        |
| Fire Tested to             | BS EN 13501-1 Class Dfl - s1                                                     |
| COO (Country of Origin)    | CN                                                                               |
| Guarantee                  | 2 years when used in a dry environment                                           |

## Additional Information



Orthomat Premium Fire Test BS EN 13501



Orthomat Premium Fire Test EN ISO 9239



Orthomat Premium Fire Test EN ISO 11925

