



TECHNICAL PRODUCT DATASHEET





UPDATED: 03/2020 ISSUE: 1

JAVA SPORT™

Java Sport™ Safety Glasses.

Modern wraparound design and styling. Hard coated anti-fog lenses. Class 1optical for all day use. Offers protection against particle impact at extreme temperatures. Economical stylish protection. Soft TPR sidearms for secure fit.






TECHNICAL INFORMATION REF CODE LENS ANTI-FOG EN 166 EN 170 EN 172 **Ø** Ø JAVA SPORT-CL CLEAR 2C-12 **Ø** JAVA SPORT-SM SMOKE 1FT Ø 5-3.1



TECHNICAL INFORMATION				
ORDER REF #	EY/UC/GL/JAVASPORT/colour			
LENS AVAILABLE	Clear, Sm oke			
PACKING	PER BOX: 12	PER CASE: 300		
SIZES AVAILABLE	ONE SIZE			
EU TYPE CERTIFICATION BY	CERTOTTICA Scarl, Zona Industriale Villanova, 32013 Longarone (BL) Italy (Notified Body No. 0530)			

CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)
EN166:2001
EN 166 1FT Suitable for continuous use (Class 1optical) Low energy impact at -5°C to +55°C (resists a 6 mm, 0.86g ball bearing at 45 m/s) (Maxim umprotection level available for glasses with sidearms)
Additional Standards: SMOKE LENS ONLY: EN 172:1994 "Solar protection filters for industrial use", Shade 5-3.1 CLEAR LENS ONLY: EN 170:2002 "Ultraviolet Filters", Shade 2C-1.2.
CAT II





l Fax: +44 (0)1902 451 271

Email: sales@ ultim a teindustrial.co.uk

Web: www.ultimateindustrial.co.uk



Registered in England No. 2035621





TECHNICAL PRODUCT DATASHEET

SAFETY GLASSES



UPDATED: 03/2020 ISSUE: 1

STANDARDS INFORMATION

EN166 - BASIC STANDARD SPECIFICATIONS

Property	Details	Frame Marked	Lens Marked	What it means in practice
	Class 1	•	1	Suitable for continuous use (all UCi eyewear is Class 1)
Optical	Class 2	•	2	Suitable for intermittent use
	Class 3	•	3	Suitable for occasional use, but must NOT be worn continuously

FRAME MARKING

Property	Details	Frame Marked	Lens Marked	What it means in practice	
	Low Energy Impact	F	F	Will resist a 6 mm, 0.86 g ball travelling at 45 m/s. This is usually the maximum for safet glasses having side arms.	
Mechanical	Medium Energy Impact	В	В	Will resist a 6 mm, 0.86 g ball travelling at 120 m/s. This is usually the maximum for safety goggles and Industrial visors	
	High Energy Impact	Α	Α	Will resist a 6 mm, 0.86 g ball travelling at 190 m/s. This is usually the maximum for specialist safety visors (polycarbonate).	

LENS MARKING

Scale Number (Filters Only)	Makers Mark	Optical Class	Mechanical Strength	Fields of Use	Scratch Resistant	Fog Resistant	Radiant Heat
5 - 1.1	UCI	1	В	3	К	N	Т

FURTHER INFORMATION

STORAGE / TRANSPORT: This product should be stored at a temperature 0-35C and 30-70% RH and kept away from solvents, or solvent vapors or any corrosive materials, as these may seriously reduce the impact protection provided by the spectacle. During transportation, ensure the product is well packaged to prevent damage. NOTE: Eye protection is only effective if correctly selected, fitted and worn for the complete period of exposure to hazards - Read ALL instructions and warnings carefully before use and consult a professional. Inspect and replace at regular intervals.

CLEANING: This product can be cleaned with soap and warm water or, if required, disinfected with a UV lamp or cleaned with a common domestic disinfectant. The lenses are coated to provide a certain level of scratch resistance, however, they are not scratch proof and it is recommended that wiping of the lens is to be kept to a minimum and only done so with a soft non-abrasive cloth. **WARNING:** This product offers no protection against IR radiation. This product offers adequate protection against UV sun radiation but should not be used against hazardous levels.

For more information about this product, or to access the Declaration of Conformity or Product Certification, visit; https://www.ultimateindustrial.co.uk/product/718-Java-Sport-CL

If appropriate to the product, EC.E.U Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address(s) or by contacting UCi customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCi are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCi assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks or registered trademarks of their respective holders. © UCi Limited, 2018





l Fax: +44 (0)1902 451 271



Web: www.ultimateindustrial.co.uk

