



## M18 B2

## M18™ 2.0 AH BATTERY

- Sophisticated electronics: REDLINK™ intelligence
- Overload protection Prevents user from damaging their cordless power tool investment in abusive situations
- Temperature management system Keeps battery in ideal temperature range to provide maximum life
- Individual cell monitoring Ensures optimal charge and discharge for maximum life
- Up to 2X more run time, 20% more power, and Up to 2X more recharges\*
- \*Compared with other Lithium-Ion technologies and / or with previous MILWAUKEE® battery technology. Results depend on voltage, tool, and application.
- Integrated weld frame
- Cell separator





Battery pack capacity (Ah) 2.0  Charge time M12_18 AC 40 min  Charge time M12_18 C 40 min  Charger 40 min  Charge time M12_18 FC 26 min  Charger The M1418C6 40 min  Charger Union M1418C6 40 min  Article Number 4932430062		
Charge time M12_18 C charger  Charge time M12_18 FC charger  Charge time M12_18 FC charger  Charge time M1418C6 charger  Weight (kg)  40 min  40 min  40 min	Battery pack capacity (Ah)	2.0
Charge time M12_18 FC charger  Charge time M1418C6 charger  Weight (kg)  40 min  40 min  40 min		40 min
charger 26 min  Charge time M1418C6 40 min  charger  Weight (kg) 0.4	_	40 min
Charger Weight (kg) 0.4	_	26 min
		40 min
Article Number 4932430062	Weight (kg)	0.4
Aitible Nullibei 4902400002	Article Number	4932430062