

| Code | PB226-BLK | | | | | | | | | | |
|-------------------------|---|---------------|----|----|----|----|--|--------|--|--|---|
| Standard | EN ISO 20345:2011 S3 HRO SRC | | | | | | | | | | |
| Name / Description | Aries – PU/Rubber Gibson Shoe | | | | | | | SAFETX | | | |
| Weight | 610 grams | | | | | | | | | | 2 |
| Colour | Black | | | | | | | | | | |
| Sizes | 6 7 | 8 9 | 10 | 11 | 12 | 13 | | | | | |
| Properties | Upper: Breathable, Grain Leather with Leather Tongue and Collar. (Leather 1.8-2.2mm). Inner Lining: Abrasion Resistant, Moisture Wicking Textile. Toe Cap: Steel Toe Cap Resistant to 200J. Midsole: Textile Pierce Resistant Midsole – Min. 1100N. Sole Unit: Dual Density PU/Rubber Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 300°C and SRC rated Slip Resistance. Footbed: Moisture Wicking, Breathable and Washable Footbed. | | | | | | | | | | |
| Areas of Application | The Aries is suitable for areas that require hot sole contact as the rubber sole unit is resistant up to 300°C, or any heavy duty applications such as working in a machine shop where swarf can cause damage to the sole of the shoe. | | | | | | | | | | |
| Standard | EN ISO 20345:2011 C E Cat. 2 | S3 HRO SRC | | S | ٩F | E٦ | | C | | | |
| Care Instructions | For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced. | | | | | | | | | | |
| Symbols | | | | | | | | | | | |
| Contact | Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP <u>sales@performance-brands.co.uk</u> <u>www.performance-brands.co.uk</u> | | | | | | | | | | |