


Code	PB228C-BLK	
Standard	EN ISO 20345:2011 S3 HRO SRC	
Name / Description	Taurus B – Chukka Boot	
Weight	780 grams	
Colour	Black	

Sizes	3	4	5	6	7	8	9	10	11	12	13		
-------	---	---	---	---	---	---	---	----	----	----	----	--	--

Properties	<p>Upper: Breathable, Full Grain Water Repellent Leather. (Leather 1.8-2.2mm).</p> <p>Inner Lining: Abrasion Resistant, Three-Dimensional Micro-Porous Moisture Wicking Textile with High Breathability.</p> <p>Toe Cap: Steel Toe Cap Resistant to 200J.</p> <p>Midsole: Stainless Steel Midsole – Min. 1100N.</p> <p>Sole Unit: Lightweight Dual Density PU/RU Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 300°C and SRC rated Slip Resistance.</p> <p>Footbed: Moisture Wicking, Breathable and Washable Footbed.</p> <p>Additional Features: Injected PU overcap.</p>
------------	--

Areas of Application	The Taurus is suitable for most industrial applications. Typical applications include construction, engineering, mechanics, local authorities and manufacturing. The overcap makes it perfect for jobs that involve kneeling or increased abrasion to the toe area.
----------------------	---

Standard	EN ISO 20345:2011  Cat. 2	S3 HRO SRC	SAFETIX	
----------	---	---------------	----------------	--

Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.
-------------------	---

Symbols	
---------	--

Contact	Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk
---------	--