

Code	PB255C-BLK									5				
Standard	EN ISO 20345:2011 S3 SRC WR													
Name/ Description	Lyra Waterproof Chukka Boot								•					
Weight	730 grams													
Colour	Black													
Sizes	3	4	5	6	7	8	9	10	11	12	13			
Properties	Inne Wat Toe Mids Sole Sho	 Upper – Breathable Full Grain Leather. (Leather 1.8-2.2mm) Inner Lining – Abrasion Resistant Moisture Wicking Textile. Breathable and Waterproof Membrane. Toe Cap – Steel Toe Cap Resistant to 200J. Midsole – Stainless Steel Midsole – Min. 1100N. Sole Unit – Dual Density PU/PU Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance. Footbed – Moisture Wicking, Breathable, and Washable Footbed. 												
Areas of Application	The Lyra is suitable for most heavy duty applications. Typical applications include construction and general industry. The overcap makes it perfect for jobs that involve kneeling or increased abrasion to the toe area.													
Standard	2034	ISO 5:2011 C at. 2	S	3 SRC WR		S	ΑF	E.	ΓIX	K				
Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.													
Symbols														
Contact						ion, Bov <u>www.</u> r					oy, LS2	3 6LP		