

Code	PB290-BRN								W.S.	NS .				
Standard	EN ISO 20345:2011 S3 SRC							1						
Name / Description	Pictor – Dealer Boot									SAFETX				
Weight	700 grams													
Colour	Brown									101				
Sizes	6	7	8	9	10	11	12	13						
Properties	Inne Toe Mid: Sole Prop Res	Upper: Breathable, Full Grain Leather. (Leather 1.8-2.2mm). Inner Lining: Abrasion Resistant, Moisture Wicking Textile. Toe Cap: Steel Toe Cap Resistant to 200J. Midsole: Stainless Steel Resistant Midsole – Min. 1100N. Sole Unit: Lightweight Dual Density PU/PU Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance. Footbed: Moisture Wicking, Breathable and Washable Footbed.												
Areas of Application	The Pictor is suitable for most industrial applications. Typical applications include construction, warehousing, manufacturing and distribution.													
Standard	2034	ISO 5:2011 E at. 2	S	3 SRC		S/A	F	E٦	Γ i)	X				
Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.													
Symbols														
Contact	Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk													