


Name	PB 42LC	
Standard	EN ISO 20345:2011 S3 SRC	
Description	Tan Lined Rigger Boot	
Weight	800 grams	
Colour	Tan	

Sizes	5	6	7	8	9	10	11	12	13				
-------	---	---	---	---	---	----	----	----	----	--	--	--	--

Properties	<p>Upper – Breathable Full Grain Leather. (Leather 1.8-2.2mm) Inner Lining – Synthetic Fur. Toe Cap – Steel Toe Cap Resistant to 200J. Midsole – Stainless Steel Midsole – Min. 1100N. Sole Unit – Dual Density PU/PU Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance. Footbed – Moisture Wicking, Breathable, and Washable Footbed.</p>
------------	---

Areas of Application	<p>The PB 42LC is suitable for most heavy duty applications. Typical applications include construction and general industry. The over cap makes it perfect for jobs which involve kneeling as the cap prevents the leather from being worn away from the toe of the boot.</p>
----------------------	---

Standard	<p>EN ISO 20345:2011  Cat. 2</p>	S3 SRC	
----------	---	--------	--

Care Instructions	<p>For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.</p>
-------------------	--

Symbols	
---------	--

Contact	<p>Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk </p>
---------	---