

Code	PB52-BLBU									Va						
Standard	EN ISO 20345:2011 S3 SRC															
Name / Description	Tornado Low FG – Lightweight Non- Metal Trainer									A A A A A A A A A A A A A A A A A A A						
Weight	500 grams															
Colour	Blac	k/Blue	)					C. C.	CO Section							
Sizes	3	4	5	6	7	8	9	10	11	12	13					
Properties	Upper: Breathable, Full Grain Leather with Textile Tongue and Collar. (Leather 1.8-2.0mm). Inner Lining: B-dry Abrasion Resistant, Moisture Wicking Textile. Toe Cap: Lightweight Fibre Glass Toe Cap Resistant to 200J. Midsole: Textile Pierce Resistant Midsole – Min. 1100N. Sole Unit: Lightweight, Injected Dual Density PU/PU Soling System with Antistatic Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance. Footbed: Moisture Wicking, Breathable and Washable Footbed.															
Areas of Application	The Tornado Low FG is a lightweight, non-metal trainer suitable for use in airports, security areas, or any environment where metal detectors are present. It is also suitable for use in a variety of industrial applications such as warehousing, distribution, manufacturing, security, transport and offices.															
Standard	EN ISO 20345:2011  C Cat. 2  S3 SRC  PRODUCT PERFORMANCE PASSION															
Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.															
Symbols																
_	Perfor	mance	Brands	Ltd, The	e Pavilio	on, Bow	liffe Ha	ıll, Bram	ıham. W	etherb	, LS23	6LP				
Contact					Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP   sales@performance-brands.co.uk   www.performance-brands.co.uk											