

Code	PB94C-BLK													
Standard	EN ISO 20345:2011 S3 HRO HI CI SRC													
Name / Description	Ankle Length Welders Boot													
Weight	750 grams													
Colour	Black *Available in sizes 6.5 and 10.5													
Sizes	3	4	5	6*	7	8	9	10*	11	12	13			
	Upper: Full Grain Barton Print Buffalo Leather with Special Heat Resistant properties. (Leather 1.8-2.0mm) Inner Lining: Moisture Wicking Textile to Vamp only.													

**Properties** 

Toe Cap: Steel Toe Cap Resistant to 200J.

**Midsole:** Textile Puncture Resistant Protective Midsole – Min. 1100N. **Sole Unit:** Dual Density Rubber/Rubber Soling System with Anti-static Properties,

Shock Absorption, Heat Resistance to 300°C and SRC rated Slip Resistance.

Footbed: Moisture Wicking, Breathable and Washable Footbed.

Additional Features: Para Aramid Flame resistant stitching, Velcro Quick

Release Fastening.

Areas of Application

The PB94C is suitable for use in welding environments where there is a high risk of it coming into contact with hot sparks. Made using only full grain leather, Para Aramid stitching and a textile lining, this product is highly flame resistant and can be used for a variety of welding applications. Overcap protects leather from wearing away when kneeling.

**Standard** 

EN ISO 20345:2011

(

Cat. 2

S3 HRO HI CI SRC



Care Instructions

For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.

**Symbols** 















Contact

Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP | sales@performance-brands.co.uk | www.performance-brands.co.uk |