

Product RE-ODOUR
 Revision date 21 June 2017
 Revision 1



Safety Data Sheet (SDS)

Section 1: Identification of the substance/preparation and of the company/undertaking

1.1 Product identifier

Product name RE-ODOUR
Product no. DISREODOR
Synonyms, Trade names No information available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning agent.
Uses advised against Any other purpose.

1.3 Details of the supplier of the safety data sheet

Supplier Kitchenmaster NI Ltd
 11 Comber Road
 Belfast
 BT8 8AN
 United Kingdom
 Tel: 028 9081477 02890812881
 sales@kitchenmaster-ni.com

Contact person

1.4 Emergency telephone number

Emergency telephone Emergency Telephone Number: 028 9081 4777 08:30 - 17:00 Monday to Thursday 08:30 - 16:30 Friday

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)
 Physical and chemical hazards Not classified
 Human health Skin Irrit.2 - H315, Eye Dam. 1 - H318
 Environment Not classified

2.2 Label elements

Contains didecyldimethylammonium chloride
 Alcohols, C12-15, ethoxylated

Label in accordance with (EC) no. 1272/2008



Signal word Danger

Hazard statements H315 Causes skin irritation.
 H318 Causes serious eye damage.

Precautionary statements

Prevention

P280 Wear protective gloves/ protective clothing/eye protection/face protection.

Response

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER or doctor/physician.
 P332 + P313 If skin irritation occurs: Get medical advice/attention.
 P362 Take off contaminated clothing and wash before reuse.

2.3 Other hazards

None known.

Section 3: Composition/identification of ingredients

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Reg. EU 1272/2008	%
didecyldimethylammonium chloride	CAS-No.: 7173-51-5 EC No.: 230-525-2	Acute Tox 4 - H302, Skin Corr. 1B - H314	1-10%
Alcohols, C12-15, ethoxylated	CAS-No.: 68131-39-5 EC No.: 500-195-7	Eye Dam. 1 - H318, Aquatic Acute 1 - H400, Aquatic Chronic 3 - H412	1-10%
propan-2-ol isopropyl alcohol isopropanol	CAS-No.: 67-63-0 EC No.: 200-661-7	Flam. Liq 2- H225, Eye Irrit.2A - H319, STOT SE 3 - H336	1-10%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives. The PBT Expert Working Group of the Technical Committee of New and Existing Chemicals in its May 2007 meeting concluded that the following product is a very persistent and very bioaccumulative substance: 5-tert-butyl-2,4,6-trinitro-m-xylene (Musk xylene, EC No: 201-329-4, Cas No: 81-15-2.) This product contains (a) substance(s) included on the candidate list according to article 59 (1,10) of regulation EC No. 1907/2006 ('REACH'). 5-tert-butyl-2,4,6-trinitro-m-xylene (Musk xylene, EC No: 201-329-4, Cas No: 81-15-2.)

Section 4: First aid measures

4.1 Description of first aid measures

General information

Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue.

Inhalation

Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

Ingestion

If this product is ingested, remove victim immediately from source of exposure. Rinse mouth thoroughly. Do not induce vomiting. Provide fresh air, warmth and rest. Get medical attention. Never give anything by mouth to an unconscious person.

Skin contact

Remove victim immediately from source of exposure. Remove contaminated clothing, shoes and jewelry and wash before reuse. Wash the skin immediately with water. Obtain medical attention if irritation persists or if blistering occurs.

Eye contact

Do not rub eye. If this product contacts the eyes, gently flush eyes with water for at least fifteen (15) minutes, lifting the upper and lower eyelids occasionally. Remove contact lenses if present and easy to do so. Avoid contaminating unaffected eye. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

Inhalation of mist or vapor may cause respiratory tract irritation.

Ingestion

Exposure to liquid product may cause irritation to mouth, throat and esophagus.

Skin contact

Contact with skin may cause irritation.

Eye contact

Causes severe eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician

Treat symptomatically.

Section 5: Fire-fighting measures

5.1 Extinguishing media

Extinguishing media	Use fire-extinguishing media appropriate for surrounding materials. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	High volume water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products	During fire, toxic gases (CO, CO ₂) are formed.
Unusual fire & explosion hazards	No unusual fire or explosion hazards noted.
Specific hazards	Fire creates: Carbon monoxide (CO). Carbon dioxide (CO ₂). In the event of damage to packaging, floors may become slippery, avoid falls.

5.3 Advice for firefighters

Special fire fighting procedures	If possible, fight fire from protected position. Avoid breathing fire vapours. Ventilate closed spaces before entering them. Containers close to fire should be removed immediately or cooled with water if safe to do so.
Protective equipment for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Eliminate all sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. In case of inadequate ventilation, use respiratory protection. Do not touch or walk through spilled material. If necessary evacuate surrounding areas.
For emergency responders	Follow safe handling advice and personal protective equipment recommendations for normal use of product.

6.2 Environmental precautions

Environmental precautions	Do not discharge onto the ground or into water courses.
----------------------------------	---

6.3 Methods and material for containment and cleaning up

Spill clean up methods	Stop leak if possible without risk. DO NOT touch spilled material! When dealing with a spillage, wear necessary protective equipment. Absorb spillage with non-combustible, inert absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. Wash thoroughly after dealing with a spillage. Floors may become slippery, avoid falls.
-------------------------------	---

6.4 Reference to other sections

Reference to other sections	See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.
------------------------------------	--

Section 7: Handling and storage

7.1 Precautions for safe handling

Handling	Read and follow manufacturer's recommendations. Use proper personal protection when handling (refer to Section 8). Do not handle broken packages without protective equipment. Do not use contact lenses. Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Do not eat, drink or smoke when using the product. Wash thoroughly after handling.
-----------------	---

7.2 Conditions for safe storage, including any incompatibilities

Storage precautions	Keep upright, locked up and out of reach of children. Keep the product in its original container. Store in cool dry areas away from direct sunlight or sources of ignition. Keep
----------------------------	--

Storage class away from oxidizing agents and acids.
Corrosive storage.

7.3 Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.
Usage description Use only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection

8.1 Control parameters

Component	STD	TWA (8 Hrs)		STEL (15mins)		Notes
propan-2-ol isopropyl alcohol isopropanol	OEL	200 ppm		400 ppm		
propan-2-ol isopropyl alcohol isopropanol	WEL	400 ppm	999 mg/m ³	500 ppm	1250 mg/m ³	

Ingredient comments WEL - Workplace Exposure Limits - EH40/2005 Workplace exposure limits.
OEL - Occupational Exposure Limit - Ireland, Occupational Exposure Limits 2016.

8.2 Exposure Controls

Protective equipment



Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Respiratory equipment

If ventilation is inadequate, suitable respiratory protection must be worn. EN 136/140/145/143/149. The specific respirator selected must be based on contamination levels found in the work place. Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN143 should be used, and suitable respirator cartridges as a backup to engineering controls. Recommended: Respirator with combination filter for organic vapour/particulate (EN 141). Consult manufacturer for specific advice.

Hand protection

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be inspected prior to use. Suggested material: Nitrile. Breakthrough time: >480 minutes. Layer thickness: 0.11 mm. Consult manufacturer for advice.

Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Eye protection

Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).

Other protection

The selected clothing must satisfy the European norm standard EN 943. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Hygiene measures

Observe normal hygiene standards. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash hands after use.

Process conditions

Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Liquid.
Colour Bright Pink.

Odour	Bubble gum.
Odour threshold - lower	No information available.
Odour threshold - upper	No information available.
pH-Value, Conc. Solution	6.50
pH-Value, Diluted solution	No information available.
Melting point	No information available.
Initial boiling point and boiling range	No information available.
Flash point	No information available.
Evaporation rate	No information available.
Flammability state	No information available.
Flammability limit - lower(%)	No information available.
Flammability limit - upper(%)	No information available.
Vapour pressure	No information available.
Vapour density (air=1)	No information available.
Relative density	0.998kg/m ³ @ 20.00 °C
Bulk density	No information available.
Solubility	Soluble in water.
Decomposition temperature	No information available.
Partition coefficient; n-Octanol/Water	No information available.
Auto ignition temperature (°C)	No information available.
Viscosity	No information available.
Explosive properties	Not classified as explosive.
Oxidising properties	No information available.

9.2 Other information

Molecular weight	No information available.
Volatile organic compound	No information available.
Other information	None noted.

Section 10: Stability and reactivity

10.1 Reactivity

Reactivity	Reaction may occur with strong oxidizing agents.
-------------------	--

10.2 Chemical stability

Stability	Stable under normal temperature conditions and recommended use.
------------------	---

10.3 Possibility of hazardous reactions

Hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
----------------------------	---

Hazardous polymerisation Will not polymerise.
Polymerisation description Not applicable.

10.4 Conditions to Avoid

Conditions to avoid Heat, sparks, open flames, temperature extremes and direct sunlight.

10.5 Incompatible materials

Materials to avoid Do not mix with other chemicals unless listed on directions.

10.6 Hazardous decomposition products

Hazardous decomposition products When heated, vapours/gases hazardous to health may be formed.

Section 11: Toxicological information

11.1 Information on toxicological effects

Toxicological information No toxicological data available for this product.

Acute toxicity (Oral LD50) No information available.
Acute toxicity (Dermal LD50) No information available.
Acute toxicity (Inhalation LD50) No information available.

Serious eye damage/irritation Causes severe eye damage.

Skin corrosion/irritation No information available.

Respiratory sensitisation No information available.
Skin sensitisation No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Specific target organ toxicity - Single exposure:
STOT - Single exposure No information available.
Specific target organ toxicity - Repeated exposure:
STOT - Repeated exposure No information available.

Inhalation Inhalation of mist or vapor may cause respiratory tract irritation.
Ingestion Exposure to liquid product may cause irritation to mouth, throat and esophagus.
Skin contact Contact with skin may cause irritation.
Eye contact Causes severe eye damage.
Waste management When handling waste, consideration should be made to the safety precautions applying to handling of the product.

Routes of entry No information available.
Target organs Eyes and skin.

Aspiration hazards: No information available.
Reproductive toxicity: No information available.

Name	LD50 oral	LD50 dermal	LD50 inhalation
didecyldimethylammonium chloride	645.00mg/kg Rat		
propan-2-ol isopropyl alcohol isopropanol	4570.00mg/kg Rat	13400.00mg/kg Rabbit	30.00mg/l (vapours) Rat 4 Hours
Alcohols, C12-15, ethoxylated	>5000.00mg/kg Rat		

Section 12: Ecological information

12.1 Toxicity

Acute toxicity - Fish DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS 7173-51-5) LC50: (96 hours) 0.32 mg/l, Lepomis macrochirus (Bluegill). Miscellaneous information sources.

Acute toxicity - Aquatic invertebrates	DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS 7173-51-5) EC50: (48 hours) 0.92 mg/l, Daphnia magna. Miscellaneous information sources.
Acute toxicity - Aquatic plants	No information available.
Acute toxicity - Microorganisms	No information available.
Chronic toxicity - Fish	No information available.
Chronic toxicity - Aquatic invertebrates	No information available.
Chronic toxicity - Aquatic plants	No information available.
Chronic toxicity - Microorganisms	No information available.
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Eco toxicological information	No ecological toxicity available on the overall finished product.

12.2 Persistence and degradability

Degradability	No information available.
Biological oxygen demand	No information available.
Chemical oxygen demand	No information available.

12.3 Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
Bioaccumulation factor	No information available.
Partition coefficient; n-Octanol/Water	No information available.

12.4 Mobility in soil

Mobility	Soluble in water.
-----------------	-------------------

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	The PBT Expert Working Group of the Technical Committee of New and Existing Chemicals in its May 2007 meeting concluded that the following product is a very persistent and very bioaccumulative substance: 5-tert-butyl-2,4,6-trinitro-m-xylene (Musk xylene, EC No: 201-329-4, Cas No: 81-15-2.)
---	--

12.6 Other adverse effects

Other adverse effects	No information available.
------------------------------	---------------------------

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
Alcohols, C12-15, ethoxylated	LC50 96 Hours >2.00ppm Brachydanio rerio (Zebra Fish)		

Section 13: Disposal considerations

Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product.
-------------------------	--

13.1 Waste treatment methods

Disposal methods	Dispose of waste and residues in accordance with local authority requirements.
-------------------------	--

Section 14: Transport information

14.1 UN number

UN no. (ADR)	Not applicable.
UN no. (IMDG)	Not applicable.
UN no. (IATA)	Not applicable.

14.2 UN proper shipping name

ADR proper shipping name	Not applicable.
IMDG proper shipping name	Not applicable.
IATA proper shipping name	Not applicable.

14.3 Transport hazard class(es)

ADR class	Not applicable.
IMDG class	Not applicable.
IATA class	Not applicable.

Transport labels	Not applicable
------------------	----------------

14.4 Packing group

ADR/RID/ADN packing group	Not applicable.
IMDG packing group	Not applicable.
IATA packing group	Not applicable.

14.5 Environmental hazards

ADR	No
IMDG	No
IATA	No

14.6 Special precautions for user

EMS	Not applicable.
Emergency action code	Not applicable.
Hazard no. (ADR)	Not applicable.
Tunnel restriction code	Not applicable.

14.7 Transport in bulk according to annex II of MARPOL73/78 and the IBC code**Section 15: Regulatory information****15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture**

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 453/2010 of 20th May 2010 amending regulation (EC) No 1907/2006.
Approved code of practice	2016 Code of Practice for the Chemical Agents Regulations in accordance with section 60 of the Safety, Health and Welfare at Work Act 2005 (No. 10 of 2005). EH40/2005 Workplace exposure limits.
Chemical safety assessment	No chemical safety assessment has been carried out.

Section 16: Other information

General information	This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.
Revision comments	This is a first issue.
Revision date	21 June 2017
Revision	1
Safety data sheet status	Approved.

Hazard statements in full

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.

H336	May cause drowsiness or dizziness.
H315	Causes skin irritation.
H201	Explosive; mass explosion hazard.
H351	Suspected of causing cancer .
H410	Very toxic to aquatic life with long lasting effects.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.