

NEW



PPE Regulation (EU) 2016/425
 EN ISO 21420:2020- Sizing & Dexterity: PASS
 EN 388:2016+A1:2018 - Protection Against Mechanical Hazards
 EN ISO 374-1:2016+A1:2018/Type A
 EN ISO 374-4:2019 % Degradation
 EN ISO 374-5:2016 - Fungi, bacteria & viruses

PRODUCTION INFORMATION

Heavyweight Latex Pro

Description: Offering the highest level of chemical resistance our type A Heavyweight Pro are the perfect glove. With excellent grip these gloves are ideal for chemical handling and industrial cleaning tasks.

- EN 388:2016+A1:2018 levels 2-0-2-0-X
- EN ISO 374-1:2016+A1:2018 Type A
- EN ISO 374-5:2016
- Protection against Bacteria and Fungi
- Protection against Viruses
- Anti slip pattern for good grip in wet and dry conditions
- Anatomically shaped for comfort
- Flocked lined
- Length 33cm
- Smooth surface
- Easy donning and doffing

Type:

- Natural rubber
- Flocked lined

Applications:

Tasks with janitorial & hygiene, waste management, chemical handling, laboratory

Packaging:

1 pair per bag - 12 pairs per master poly - 12 bags per case

Product Codes:

SPG-55171-5 S - 2XL Heavyweight Latex Pro

Colourways:

Black

	EN ISO 374-1:2016+A1:2018 Type A	Levels	EN ISO 374-4:2019
A	Methanol	2	-6.3%
K	Sodium Hydroxide 40%	6	-3.0%
L	Sulphuric acid 96%	4	27.6%
M	Nitric acid 65%	6	10.3%
N	Acetic acid 99%	2	19.9%
O	Ammonium hydroxide 25%	1	-25.4%
P	Hydrogen peroxide 30%	6	6.4%
S	Hydrofluoric acid 40%	6	X
T	Formaldehyde 37%	6	-9.2%

Standards:

CE 0598 UK CA 0120

EN 388:
2016+A1:
2018



Abrasion: 2
 Blade Cut: 0
 Tear: 2
 Puncture: 0
 ISO Cut level: X

EN ISO 374-5:
2016




VIRUS

EN ISO 374-1:
2016+A1:2018
/Type A



Product does
contain latex



Size Chart:

Measurements in mm	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)
Hand Length (A)	171	182	192	204	215
Hand Circumference (B)	178	203	229	254	279

The information shown on this specification sheet is intended as a guide and is advisory only. All details were correct at the time of issue. As conditions of use are ultimately beyond our control, we advise that the product is tested for the particular application before use.

Issue No.: 1

Issue Date: 06.10.2022