

FEATURES

- Cut resistant (EN388: Level 5)
- Durable foam nitrile palm coating grips in dry, damp and light oily conditions
- Excellent dexterity
- Medium weight feel
- Breathable materials
- Knitwrist cuff style

DESCRIPTION

- HPPE/Glass liner
- Foam nitrile coating



TECHNICAL DATA

AVAILABLE SIZES

7/S • 8/M • 9/L • 10/XL

PACKAGING

Pairs per pack/box

10/120

COLOUR OF LINER/COATING

Grey/Black

TYPICAL APPLICATIONS

- Automotive
- Construction
- Engineering
- Logistics
- Metal Fabrication and Handling
- Waste Management

Cat

CE

II



EN 388 standard

Abrasion	4
Cut	5
Tear	4
Puncture	3

EN388: 2003



4543

Recommendations For Use

- Do not use near moving machines if there is a risk of entanglement.
- Storage: Gloves should be ideally stored in cool, dry conditions in original packaging and away from direct sunlight.
- Cleaning/Maintenance: Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. If appropriate, decontamination may take place under lukewarm water using laundry soap and detergent. Don't use chlorine bleaches.

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Trafford Park, Manchester, M17 1NY, United Kingdom

Tel: 0161 877 4747 Fax: 0161 877 4746 Web: www.globus.co.uk

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

EC compliance certificate delivered by the notified body, SATRA Technology Centre Ltd., Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Notified Body No. 0321)



GLOBUS_TONS-DATA-TF-5-0915