



FROM TYVEK[®] CLASSIC TO... TYVEK[®] CLASSIC XPERT

Decades of experience in the field have made Tyvek[®] Classic a point of reference in chemical protective clothing.

By continuing to improve, to fine-tune and to innovate, DuPont has pushed the Tyvek[®] Classic to a new level of protection:

Tyvek[°] Classic Xpert, setting a new standard of protection in the type 5/6 category.



NEW

REDEFINING PROTECTION IN EVERY DETAIL

Tyvek[®] Classic Xpert lifts the type 5/6 category to a higher standard!



- ✓ main a straight of the s
- ✓ ∑tra particulate protection
- ✓ main a comfort



REDEFINING PROTECTION IN EVERY DETAIL

→ more protection: 3X more protective!

- Offers superior liquid protection thanks to a new patent pending seam technology
- Passes the new and more stringent type 6 norm against liquids'
- Demonstrates significantly less leakage than conventional stitched seams even under the new and more aggressive type 4 test.²

Look at other suits: you'll notice almost always that holes start to appear when the seams are stretched!

Tyvek® Classic Xpert seam structure




Conventional stitched seam structure



→ Xtra particulate protection

Tyvek[®] Classic Xpert also benefits from enhanced particulate protection compared to any coverall of its category.

6 *** more** particulate protection than Tyvek[®] Classic! **10 * more** particulate protection than microporous films! Particulate nominal protection factor (EN 1073-2:2002): reaches now class 2!





Setting a new standard, Tyvek[°] Classic Xpert launches a whole new era of liquid and particulate protection.

0

EN ISO 17491-4 Method A:2008, whole suit low-level spray test

EN ISO 17491-4 Method B:2008, whole suit high-level spray test (2.5x more liquid than method A)

EN ISO 13982-2:2004, Inward leakage of aerosols of fine particles into suits

TILE = Total Inward Leakage per activity, i.e. % leakage into suit. Values shown are the highest mean value of inward leakage for one activity

according to EN 1073-2 (suits taped at mask, ankles, cuffs and flap).



CEPTIONAL DESIGN, X TRA FLEXIBILITY

Offering more protection, Tyvek[®] Classic Xpert benefits also from a new ergonomic design allowing full freedom of movement even when performing strenuous tasks:

Tyvek[®] Classic **%**pert features include:



*Fabric only

Tested and approved by PERIENCE THE NEW TYVEK® CLASSIC XPERT NOW!

www.dpp-europe.com/TyvekClassicXpert/

QUPOND

Tyvek₀ ClassicXpert

Xpertise in one call!

Your

Order

 Benefit from our FREE technical service for your chemical protective clothing selection, the 'Techline', that is here to support you! Tel: +352 621 164 043 Website: www.dpp-europe.com/technicalsupport

Order your FREE sample

For more information on our support services: DuPont Personal Protection

DuPont de Nemours Luxembourg S.àr.l. L-2984 Luxembourg Tel.: +800 3666 6666 (international toll-free) Fax: +352 3666 5071 E-mail: personal.protection@lux.dupont.com Or visit our website at:

www.dpp-europe.com/TyvekClassicXpert/

This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience becomes available. DuPont does not guarantee results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. This information is intended for use by personsibility to technical expertise to undertake evaluation under their own specific end-use conditions, at their own discretion and risk. Anyone intending to use this information shuld first check that the garment selected is suitable for the intended use. The end-user should discontinue use of garment if fabric becomes torn, worn or punctured, to avoid potential chemical exposure. Since conditions of use are beyond our control, we make no warranties, expressed or implied, including but not limited to warranties of merchantability or fitness for a particular purpose and assume no liability in connection with any use of this information. This information is not intended as a licence to operate under or a recommendation to infringe any patent or technical information of DuPont or other persons covering any material or its use.

