

## Product Description

- Cut 1, 15 gauge Nylon liner
- Waterproof - Double dipped
- Fully coated in Smooth Latex, finished with a Sandy Latex palm dip
- Suitable for use inside or outside, in wet or dry; cold or warm conditions
- Superb wet or dry grip
- Elasticated cuff with coloured cuff size indicator
- Meets the requirements for resistance to water ingress (ISO15383)

## Specifications

<b>Code:</b> WS1	<b>Size Range:</b> 7 to 11
<b>Liner:</b> Nylon	<b>Pack Size:</b> 10 pairs
<b>Gauge:</b> 15	<b>Case Size:</b> 120 pairs
<b>Coating:</b> Sandy Latex	<b>EN388:</b> 2141X

## Suggested Applications

- Construction
- Scaffolding
- Infrastructure
- Banksmen
- Engineering
- Landscaping
- General Handling/Lightweight Applications

## Certification and Marking



## Limitations of Use

<b>Maintenance</b>	Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Only properly fitting gloves guarantee protection and grip.
<b>Storage</b>	Store at normal room temperature in a dry, well ventilated area. Avoid direct heat radiation.
<b>Disposal</b>	Used gloves can be contaminated. Dispose with household waste or as instructed by your local authority.
<b>Cleaning</b>	Do not wash. The performance of the product after laundering is unknown. Beat or brush out after each use, depending on level of dirt.
<b>Durability</b>	The period of use depends on the degree or intensity of use in the retrospective application. It is therefore not possible to provide a 'life span' of the gloves.
<b>Note</b>	Due to the nature of this product the user is advised to carry out their own risk assesment before use, depending on application.
<b>Warning</b>	<b>This product contains natural rubber latex which could cause anaphylactic responses.</b>