

# HyFlex<sup>®</sup>

ADVANCED MECHANICAL PROTECTION

## 11-561

All-day comfort & cut protection



Cut



Light Duty

## The thinnest, lightest EN ISO C/ANSI A3-level industrial gloves, offering 100% greater durability\*

- **Optimized durability:** Hyflex<sup>®</sup> 11-561 industrial safety gloves are 100% more durable than nearest competitors, with FORTIX<sup>™</sup> Abrasion Resistance Technology
- **Advanced protection:** These safety gloves' patented INTERCEPT<sup>™</sup> Cut Resistance Technology guards against lacerations
- **Enhanced features:** The 11-561's palm-dipped coating improves grip, while a reinforced thumb crotch defends against rapid wear
- **Elevated comfort:** HyFlex<sup>®</sup> 11-561 industrial working gloves are also light and thin, making them flexible, yet protective
- **Certified harm-free:** Dermatest<sup>®</sup> and Oeko-Tex<sup>®</sup> certification ensures these PPE gloves are skin-friendly and free of harmful substances
- **Proven excellence:** HyFlex<sup>®</sup> 11-561 PPE gloves satisfy EN and ANSI norms for cut and abrasion resistance

### Industries

- Automotive
- Machinery and Equipment
- Metal fabrication
- Mining
- Oil and gas
- Automotive Aftermarket

### Applications

- Handling metal sheets & panels
- Handling parts with sharp, rough edges
- Final assembly
- Handling materials with sharp or rough edges
- Assembly & inspection of components
- Applying finish to materials, products



# HyFlex<sup>®</sup>

ADVANCED MECHANICAL PROTECTION

## 11-561

All-day comfort & cut protection

### Key Features

- **FORTIX™ Abrasion Resistance:** EN and ANSI level 4 abrasion resistance
- **INTERCEPT™ Cut Resistance:** Better hand protection and workplace safety
- **Palm-dipped coating:** For breathable PPE gloves with superior grip \*when compared with nearest market competitors

### Technologies



DMF free



Fibre glass free



**FORTIX™**

Abrasion Resistance Technology



**INTERCEPT™**

Cut Resistance Technology

### Performance Standards & Regulatory Compliance

#### REACH Compliant



### Specifications

BRAND   STYLE	DESCRIPTION	Gauge	SIZE	LENGTH	COLOR	PACKAGE
HyFlex <sup>®</sup> 11-561	<b>Finishing:</b> Palm Coated <b>Coating Material:</b> Nitrile <b>Liner Material:</b> Nylon, HPPE, Basalt, Spandex, Polyester <b>Cuff Style:</b> Knitwrist	15	5, 6, 7, 8, 9, 10, 11, 12	210-285 mm	Grey	12 pairs/bag, 12 bags/carton

### For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### North America Region

Ansell Healthcare Products LLC  
111 Wood Avenue South,  
Suite 210  
Iselin, NJ 08830, USA  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Australia

Ansell Limited  
Level 3,678 Victoria Street,  
Richmond, Vic, 3121  
Australia  
T: +61 1800 337 041  
F: +61 1800 803 578

#### Asia Pacific Region

Ansell Global Trading Center  
(Malaysia) Sdn Bhd  
Prima 6, Prima Avenue  
Block 3512, Jaijan Teknokrat 6  
T: +603 8310 6688  
F: +603 8310 6699

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
Blvd. Bernardo Quintana No. 7001-C,  
Q7001 Torre II,  
Suites 1304, 1305 y 1306,  
Col. Centro Sur, c.p. 76079  
Queretaro, Qro. Mexico  
T: +52 442 248 1544 / 248 3133

#### Canada

Ansell Canada  
105 Lauder  
Cowansville, QC J2K 2K8  
Canada  
T: +1 800 363 8340  
F: +1 800 267 3551

Ansell, <sup>®</sup> and <sup>™</sup> are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2022 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.