



Produktfamilj

Laser Trak Detectable Earplug

Highly visible protection [visual/metal detectable]



Product Numbers &



3301167

Laser Trak - corded
SNR 35 H - 34 M - 32 L - 31

Översikt

Viktigaste egenskaperna

- Non-ferrous metal grommet and bright colors – easily detected by visual and automated inspection
- Self-adjusting polyurethane foam expands to fit virtually any wearer
- Contoured T-shape for easy insertion and wear

Rekommenderade branscher/rekommenderat användningsområde

- Livsmedel
- Läkemedel

Risker

- Buller

Föreskrifter

- 29 CFR 1910.95 - OSHA Occupational Noise Exposure (US)
- ANSI S3.19-1974 - Attenuation Test Protocol (US)
- Part II, (R.S.C. 1985, c. L-2) - Canada Labour Code
- Z94.2-1994 - Attenuation Test Protocol (CAN)
- 2003/10/EC - EU Hearing Directive
- 89/686/EEC - EU Directive/PPE
- Category II - EC Category/PPE
- EN-24869-1:1993 - EU Standards
- EN 352-2:1993 - EU Standards
- NOHSC: 1007 (2000) - National Standard for Occupational Noise (AUS/NZ)

Laser Trak Detectable Earplug

- NR 15 - Security and Health of Work, Annexes 1 and 2, n°3.214/1978 - Occupational Noise Regulations (BR)
- ANSI S12.6/1997 - Method B - Attenuation Test Protocol (BR)

Tidigare varumärke

Howard Leight

Specifikationer

Color

- Orange/Blue

Shape

- T-Shape

Material

- Polyurethane Foam/Brass

Packaging

- Polybag

Cord

- Polycord

NRR

- 32

Canada Class

- A(L)

SNR

- 35

SLC80

- 25 dB / Class 4

Certifieringarna

CE Certificate - Laser Trak

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Secured/Hearing_Protection/Earplugs/20036/1033.aspx

CE Certificate - Laser Trak

Trycksaker & dokument

Instruction Manual - Laser Trak (global)

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Hearing_Protection/Earplugs/4294986714/1033.aspx

Earplug Instruction Poster - EN

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Hearing_Protection/Earplugs/19799/1033.aspx

Earplug Instruction Poster - ES

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Hearing_Protection/Earplugs/19802/1033.aspx

Earplug Instruction Poster - FR

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Hearing_Protection/Earplugs/19800/1033.aspx

Data Sheet Howard Leight Laser Trak LT-30 - AUS

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Hearing_Protection/Earplugs/16513/1033.aspx

Noise Thermometer Poster - AUS

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Hearing_Protection/24933/1033.aspx

Earplug Fitting Poster - AUS

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Hearing_Protection/24934/1033.aspx

Care & Maintenance of Earplugs and Earmuffs - AUS

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Hearing_Protection/24936/1033.aspx

Training & Proper Use

1. With clean hands, roll the entire earplug into narrowest possible crease-free cylinder.
2. Reach over your head with a free hand, pull your ear up and back, and insert the earplug well inside your ear canal.
3. Hold for 30 – 40 seconds, until the earplug fully expands in your ear canal. If properly fitted, the end of the earplugs should not be visible to someone looking at you from the front.
4. Proper Fit – If either or both earplugs do not seem to be fitted properly, remove the earplug and reinsert.
5. Removal – Gently twist earplug while slowly pulling in an outward motion for removal.
6. Acoustical Check – In a noisy environment, with earplugs inserted, cup your hands over your ears and release. Earplugs should block enough noise so that covering your ears with your hands should not result in a significant noise difference.

Ytterligere informasjon

CARE + MAINTENANCE

- INSPECT – Inspect prior to fitting, examine your earplugs for dirt, damage or extreme hardness—discard immediately if compromised.
- DISCARD – For proper hygiene, discard Single-Use earplugs after use.
- HYGIENE – To maintain hygiene standards, Single-Use earplugs should be discarded at the end of every shift.

RELATERADE PRODUKTER