



# **SHOWA S-TEX 376**

Durability meets comfort with the 376 cut-resistant gloves. Engineered with steel-reinforced Hagane Coil® technology, the 376 offers high-performance cut protection. A dual nitrile coating provides high abrasion resistance as well as optimal wet and dry grip. The ergonomically designed hand mold reduces hand fatigue and wearer discomfort.



#### **BENEFITS**

- Hydrocarbon-resistant
- Flexible
- Form-fitting
- Cut-resistant
- · Increased dexterity
- Breathable
- Seamless knit
- Oil-resistant

#### **INDUSTRIES**



Aerospace



Automotive



Construction



Engineering



Glass



Manufacturing



Mechanical

#### **HAZARDS**



Cut

#### **FEATURES**

- Ergonomic
- 3/4 nitrile dipped with extra foam nitrile on palm
- Hagane Coil® technology
- · Rough grip





# **NORMS & CERTIFICATES**

Cat II







4X41D





ANSI/ISEA 105-2016 CUT

Cut

ANSI/ISEA 105-2016 PUNCTURE



Puncture

# **PACKAGING**

- Pair per polybag: 12Polybags per case: 10
- Pair per case: 120

#### **LENGTH**

220 - 270mm

# **COATING**

- Foam nitrile
- Nitrile

#### **LINERS**

- Cut resistant Stainless
  Steel
- Knit weight Ultra lightweight

## **SIZES**

6/S | 7/M | 8/L | 9/XL | 10/XXL

# COLOUR

- Grey
- Blue

# **TRADES & APPLICATIONS**

- Light assembly of oil-coated pieces
- Steel fabrication
- · Steel fixing
- · Handling heavy equipment
- · Handling glass and windows
- Canning
- Bottling
- HVAC

# **MATERIAL**

- Polyester
- Seamless knit
- · Stainless steel

# **USER INSTRUCTIONS**

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

#### **DISCLAIMER**

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

## **GET IN TOUCH**